

5G Flat Omni Ceiling Antenna



An ISO 9001: 2015 Certified Company



Technical Specifications

Model No.	FLOMNI5G06
Frequency Range	698-960MHz / 1710MHz - 2170 MHz / 2300-2700MHz / 3400-4000MHz
Gain	2/6 Dbi
VSWR	2.0/1.8 max
Impedance	50 Ω
Polarization	Horizontal
Inter Modulation	-150 dBc @ 2 x 33dBm IM3
Input Power max.	50 W
Radom Materia	ABS
Radom Color	White
Operation Temperature	-40~+55 °C
Environmental Class	IP65
Number of Input Ports	1
Application	Indoor
Connectors	N Type female
Pigtail Cable	Approx. 300 mm
Mounting Hardware included	Mounting Clamp
Height	18 mm
Diameter	220 mm
Width	4.3 mm
Length	4.3mm
Weight	0.3 Kg
Compliances	CE Compliant
ROHS	ROHS compliant
Brand	Gleam light India

FEATURES

2G/3G/4G/5G wireless services
Low return loss, Stable performance
Pigtail with N Female connector
Ceiling mounting

CALL OR  +91-8800386366

Follow Us For More Updates [GLEAMLIGHTINDIA](https://www.gleamlightindia.com) /     

Info@gleamlightindia.com/www.gleamlightindia.com/www.gleamindia.com

GLEAM LIGHT INDIA PRIVATE LIMITED

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

