

Flat Omni Antenna -2G/3G



An ISO 9001:2015 Certified Company



Technical Specifications

Model No.	FLATOMID20
Frequency Range	824-960/1710-2500MHz
Polarization	Vertical
Gain	2 DBI
Horizontal Lobe width	70/60°
Vertical Lobe width	55/45°
Lightning Protection	DC Ground
VSWR	≤2
Maximum Input Power	100W
Impedance	50Ω
Connector Type	N Female/ Customized
Operating Temp.	-40-60°C
Radome Material	ABS/PP
Color	White
Cable Length	200 mm/Customized
Compliances	CE Compliant
ROHS	ROHS compliant
Brand	Gleam Light India

Product Features:-

- Wide Frequency Band
- Easy to Install
- No need of Technical person
- Boost Data Downloading Speed
- Low Insertion Loss
- Low VSWR
- Light Weight

CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com/www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

GLEAM LIGHT INDIA PRIVATE LIMITED

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

