


GSM RUBBER DUCK ANTENNA



Technical Specifications:

Model No	GSMIDSMA05
Frequency Range	824~894/1710~2170 MHz
Polarization	Linear
Gain	5 DBi (Zenith)
VSWR	≤2.5
Maximum Input Power	50 W
Impedance	50Ω
Connector Type	SMA M / RP SMA M / NM /TNC M
Operating Temp	-40°to +80°C
Radome Material	ABS/PP
Radom Color	Black
Brand	Gleam Light India
ROHS	Compliant
Compliances	CE compliant



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA /**     
Info@gleamlightindia.com /www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com
12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

GSM RUBBER DUCK ANTENNA



7.12
inch



Gain 5 DBI
824-2170 MHZ

Rubber Protector, Waterproof and
Prevent from Oxidization



High-quality interface
Quality Screw interface, makes the
connection closer and signal more stable



Wide Angle
90°-180°

CONNECTOR TYPE



SMA M



RP SMA M



N M



TNC M



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     
Info@gleamlightindia.com /www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com
12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041