



An ISO 9001: 2015 Certified Company

# GSM Rubber Duck Antenna



## Technical Specifications:

Model No	GSMIDSMA09
Frequency Range	824~894/1710~2170 MHz
Polarization	Linear
Gain	9 DBI
VSWR	$\leq 2$
Maximum Input Power	50W
Impedance	50 $\Omega$
Connector Type	SMA M / RP SMA M
Operating Temp	-40 °C to +80 °C
Radome Material	ABS/PP
Radom Color	Black
ROHS	Compliant
Brand	Gleam Light India
Compliances	CE compliant

**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) / [www.gleamlightindia.in](http://www.gleamlightindia.in) / [www.gleamlightindia.com](http://www.gleamlightindia.com) / [www.gleamindia.com](http://www.gleamindia.com)

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041



# GSM Rubber Duck Antenna



**Gain 9 DBI**

**824-2170 MHZ**

Rubber Protector, Waterproof and Prevent from Oxidization



**High-quality interface**

Quality Screw interface, makes the connection closer and signal more stable



**Wide Angle**

**90°-180°**

## CONNECTOR TYPE



**RP SMA M**



**SMA M**

**CALL OR** **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) / [www.gleamlightindia.in](http://www.gleamlightindia.in) / [www.gleamlightindia.com](http://www.gleamlightindia.com) / [www.gleamindia.com](http://www.gleamindia.com)

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

