

# MIMO Ceiling Omni Antenna



An ISO 9001: 2015 Certified Company



## Technical Specifications

Model No.	MIMO04G012
Frequency Range	698-960/1710-2700MHz
Polarization	Vertical/Horizontal
Gain	12Dbi
Horizontal Lobe width	70°
Vertical Lobe width	65°
Lightning Protection	DC Ground
VSWR	≤1.5
Maximum Input Power	100 W
Impedance	50 ohm
F/B	18
Connector Type	N Female/SMA/TNC/Customized
Operating Temp	-40~+60°C
Radome Material	ABS/PP
Radome Color	White
Brand	Gleam Light India
Compliances	CE Compliant
ROHS	Compliant

## Product Features:-

- Low Profile aesthetically neutral housing
- Mounts directly and easily to ceiling tile
- Wide bandwidth 700/850/900/1800/1900/UMTS/2300/2400/2500
- Two radiating elements optimized for indoor MIMO Applications
- Low cross correlation between radiating elements

**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com/www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

