

# LTE MIMO Indoor Patch Panel Antenna For WIFI & Router



An ISO 9001: 2015 Certified Company



## Technical Specifications

Model No.	MIMO04G035
Frequency Range	798-960/1710-2700 MHz
Polarization	Vertical
Gain	35 dBi
Radiations	Omni
Lightning Protection	DC Ground
VSWR	≤2
Maximum Input Power	10W
Impedance	50Ω
Connector Type	CRC9/TS9/SMA/Customized
Operating Temp.	-40~+60°C
Radome Material	ABS/PP
Radome Color	White
Brand	Gleam Light India
Compliances	CE Compliant
ROHS	Compliant

## Product Features:-

- Compatible with 4G mobile broadband Modems router
- Simple installation
- No software required
- Usable indoor or outdoors Enhance and maintain excellent signal quality
- Light weight

**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com/www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

