

# Ceiling Omni Antenna



An ISO 9001:2015 Certified Company



## Technical Specifications

Model No.	COMNIID040
Frequency Range	698-960/1710-2700MHz
Polarization	Vertical
Gain	2/4 Dbi
Horizontal Lobe width	70/60°
Vertical Lobe width	55/45°
Lightning Protection	DC Ground
VSWR	≤1.5
Maximum Input Power	100W
Impedance	50Ω
Connector Type	N Female/SMA/TNC/ Customized
Operating Temp.	-40~+60°C
Radome Material	ABS/PP
Color	White
Cable Length	300 mm/Customized
Compliances	CE Compliant
ROHS	ROHS compliant
Brand	Gleam Light India

### Product Features:-

- Wide Frequency Band
- Easy to Install
- No need of Technical person
- Boost Data Downloading Speed
- Gain dBi-2/4 dBi
- Low VSWR
- Light Weight

**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com/www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

