

# MIMO OMNI Cylindrical Antenna



An ISO 9001:2015 Certified Company



## Technical Specifications

Model No.	MICYMNI012
Frequency Range	698-960-1710-2700 MHz
VSWR	≤1.5
Gain	12Dbi
F/B ratio	less than 18dB
Vertical Lobe Width	55/45°
Lightning Protection	DC Ground
Operating Temperature	-40~+85°C
Maximum Input Power	50W
Polarization	Vertical
Impedance	50Ω
Connector	NF/NM/SMA/Customized
Radome material	Fiberglass
Length	235 mm Approx.
Radome color	White
Mounting Method	Pole Mount
Cable Length	5 Meter X 2 /Customized
Compliances	CE Compliant
ROHS	ROHS compliant
Brand	Gleam Light India

### Product Features:-

- Multiple Frequencies Omni-directional radiation pattern Low interference
- Broad frequency range
- Durability
- Compact size

**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com/www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

