

# MIMO OMNI Cylindrical Antenna



An ISO 9001: 2015 Certified Company



## Technical Specifications

Model No.	MICYMNI018
Frequency Range	698-960-1710-2700 MHz
VSWR	≤1.5
Gain	18Dbi
F/B ratio	less than 18dB
Vertical Lobe Width	55/45°
Lightning Protection	DC Ground
Operating Temperature	-40~+85°C
Maximum Input Power	50W
Polarization	Vertical
Impedance	50Ω
Connector	NF/NM/SMA/Customized
Radome material	Fiberglass
Length	420 mm Approx.
Compliances	CE Compliant
ROHS	ROHS compliant
Radome color	White
Mounting Method	Pole Mount
Cable Length	5 Meter X 2 /Customized

### Product Features:-

- High-gain performance
- Easy installation
- Weather-resistant design
- 360° Coverage
- reduce errors
- Multiple input, multiple output (MIMO) capability

**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA**     

Info@gleamlightindia.com/www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

