

# Outdoor Patch Panel Antenna



An ISO 9001: 2015 Certified Company



## Technical Specifications

|                       |                       |
|-----------------------|-----------------------|
| Model No.             | PPAOD2G140            |
| Frequency Range       | 824-960/1710-2500 Mhz |
| Polarization          | Vertical              |
| Gain                  | 14 Dbi                |
| VSWR                  | ≤1.5                  |
| Maximum Input Power   | 50 W                  |
| Horizontal Lobe width | 60°                   |
| Vertical Lobe width   | 55°                   |
| Lightning Protection  | DC Ground             |
| Impedance             | 50 ohm                |
| Operating Temp.       | -40°C/+80°C           |
| Connector             | N Female/Customized   |
| Colour                | White                 |
| Weight                | 1 KG                  |
| Body Material         | ABS/PP                |
| Reflector             | Aluminium             |
| Dimensions            | 220X220X50 mm         |
| Mounting              | Pole Mount            |
| Radome Color          | White                 |
| RoHS                  | Compliant             |



**CALL OR**  **+91-8800386366**

Follow Us For More Updates [GLEAMLIGHTINDIA /](#)       
[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com)/[www.gleamlightindia.in](http://www.gleamlightindia.in)/[www.gleamlightindia.com](http://www.gleamlightindia.com)/[www.gleamindia.com](http://www.gleamindia.com)  
12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041