

# Patch Panel Antenna



## Technical Specifications

Model No.	PPAMST2G12
Frequency Range	698-960/1710-2700 MHz
Polarization	Vertical
Gain	10/12 dBi
Horizontal Lobe width	360°
Vertical Lobe width	55°
Lightning Protection	DC Ground
VSWR	≤1.5
Maximum Input Power	100 W
Impedance	50 ohm
Connector Type	N Female/Customized
Operating Temp.	-40~+60°C
Radome Material	ABS/PP
Radome Color	White
Cable	RG-58(Pure Copper)
Cable Length	330 mm
Weight	500 Gram
Brand	Gleam Light India
Compliances	CE compliant
ROSH	Compliant

**CALL OR**  **+91-8800386366**

Follow Us For More Updates [GLEAMLIGHTINDIA](#) /     

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) / [www.gleamlightindia.in](http://www.gleamlightindia.in) / [www.gleamlightindia.com](http://www.gleamlightindia.com) / [www.gleamindia.com](http://www.gleamindia.com)

**GLEAM LIGHT INDIA PRIVATE LIMITED**

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

